



<b>Versiune</b>	Perete 90 cm - 950 m <sup>3</sup> /h
<b>Design</b>	Falmecc Lab Professional
	Scotch brite stainless steel (AISI 304) Professional Buffle filters with liquid collector
<b>Control</b>	Panou de control electronic
<b>Modul</b>	
<b>Iluminat</b>	Dynamic LED Light (2700K - 5600K) Dimmable led lighting Led 3x1,2 W - 2700 K / 5600 K
<b>Filters</b>	Professional Baffle Filters
<b>Dimensions</b>	90 cm 52 cm 60 cm
<b>Notes</b>	From 04.11.2024 the dynamic and dimmable light is included.
	320 W
<b>Tensiune/frecvență</b>	220-240V 50-60Hz
<b>Plug</b>	Shuko
<b>Motor</b>	950 m <sup>3</sup> /h 860 m <sup>3</sup> /h I.E.C.61591 64 dB (A)re1pW I.E.C. 60704-2-13 A
	33 kg
<b>Net Weight</b>	28 kg 0.33 m <sup>3</sup> L 995 x H 562 x P 595 mm




**Accesorii optionale**

<b>Code</b>	<b>Description</b>
KACL.1032#IF	Extension H700 Wall - Inox
KACL.1033#IF	Extension H960 Wall - Inox
KACL.815	Șervețel de protecție pentru suprafețe din oțel inoxidabil (cutie 10 buc.)

Viteza motorului	1	2	3	4
	53	58	64	69
	350	470	620	860
	500	540	560	600
	185	215	240	260
leșire aer	150	150	150	150





PF		
S	Falmec Lab	
M	Perete 90 cm - 950 m3/h	
AEC	68.80	kWh/a
EEC	A	
FDE	29.30	
FDEC	A	
LE	37.00	
LEC	A	
GFE	74	
GFEC	C	
Qmin	350	m <sup>3</sup> /h
Qmax	620	m <sup>3</sup> /h
Qboost	860	m <sup>3</sup> /h
SPEmin	53	dBa
SPEmax	64	dBa
SPEboost	69	dBa
PO	0	W
PS	0.48	W
PI		
F	0.90	
EEL	54.60	
Qbep	473	m <sup>3</sup> /h
Pbep	435	Pa
Qboost	860	m <sup>3</sup> /h
Wbep	195	W
WL	6.50	W
Emiddle	157	lux
Lwa-SPEmax	64	dBa

PF\_Scheda prodotto conforme a 65/2014 S\_Supplier name / M\_Model identification / AEC\_Annual Energy Consumption (AEC hood) / EEC\_Energy Efficiency class / FDE\_Fluid Dynamic Efficiency (FDE hood) / FDEC\_Fluid Dynamic Efficiency class / LE\_Lighting Efficiency (LE hood) / LEC\_Lighting Efficiency class / GFE\_Grease Filtering Efficiency / GFEC\_Grease Filtering Efficiency class / Qmin\_Air flow (in m<sup>3</sup>/h) at min speed in normal use / Qmax\_Air flow (in m<sup>3</sup>/h) at max speed in normal use / Qboost\_Air flow (in m<sup>3</sup>/h) at intensive or boost setting (max air-flow) / SPEmin\_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax\_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost\_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0\_Power consumption in off mode (Po) / Ps\_Power consumption in stand by mode (Ps).

PI\_Additional information according to 66/2014 Calculation methods: EN 61591:2020 F\_Time increase factor / EEL\_Energy Efficiency Index / Qbep\_Measured air flow rate at best efficiency point / Pbep\_Measured air pressure at best efficiency point / Qboost\_Maximum air flow / Wbep\_Measured electric power input at best efficiency point / WL\_Nominal power of the lighting system / Emiddle\_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax\_Sound pressure level at the highest speed.