




Versiune	Perete - 85 cm - negru satinat - 800 m ³ /h
Design	Falmec Lab Design
Control	Oțel vopsit Sticlă neagră satinată Panou cu buton tactil Telecomandă (opțional) Dialogue system cu mod automat
Modul	
Masca pentru tubulatura	Ieșire din spate posibilă
Iluminat	Dimmable led lighting Dynamic LED Light (2700K - 5600K) Strip Led 5,8 W - 2700 K / 5600 K
Filters	Filtru de grăsime din metal, detașabil și lavabil Filtru Regenerable Carbon.Zeo Microtech (opțional)
Dimensions	85 cm 52 cm 52 cm
Notes	Availability Carbon.Zeo filter KACL.1039 for hoods produced from Sept. 2024
Tensiune/frecvență	280 W 220-240V 50-60Hz
Motor	800 m ³ /h 708 m ³ /h I.E.C.61591 63 dB (A)re1pW I.E.C. 60704-2-13 A
Net Weight	30 kg 25 kg 0.27 m ³ L 950 x H 442 x P 655 mm





Accessorii optionale

Code	Description
KACL.1039	Filtru Regenerabil Carbon.Zeo Microtech
KCQAN.00#N	Optional chimney (Black)
105080053	Telecomanda
KACL.1059	Deflector de aer pentru ieşire D=150mm

PF		
S	Falmec Lab	
M	Perete - 85 cm - negru satinat - 800 m3/h	
AEC	43.40	kWh/a
EEC	A	
FDE	33.30	
FDEC	A	
LE	29.60	
LEC	A	
GFE	82	
GFEC	C	
Qmin	299	m ³ /h
Qmax	584	m ³ /h
Qboost	708	m ³ /h
SPEmin	49	dBa
SPEmax	63	dBa
SPEboost	67	dBa
PO		
PS	0.28	W
PI		
F	0.80	
EEL	47.10	
Qbep	429	m ³ /h
Pbep	375	Pa
Qboost	708	m ³ /h
Wbep	134	W
WL	5.80	W
Emiddle	172	lux
Lwa-SPEmax	63	dBa

PF_Scheda prodotto conforme a 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps).

PI_Additional information according to 66/2014 Calculation methods: EN 61591:2020 F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximum air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.